

## Automatic turbidex filters TM valves



### Automatic filters features:

- Automatic cleaning valves for time.
- Vessel body made in polyester reinforced fiberglass.
- Special filters for the removal of suspended matter.
- Filter media: turbidex and gravel.
- Work pressure: 3 to 6 bar

### Valve features:

- Made of noryl
- Work temperature: 4°C to 40°C
- Power supply: 230V - 12V, 50Hz.
- No water by-pass



TM67



TM75



TM77

Ref.	Valve model	Connection	Valve flow	Wash flow	Max. service flow	Turbidex load	€/uni.
CT67001	TM67	1"	4 m³/h	1,22 m³/h	0,96 m³/h	14 L	
CT67002	TM67	1"	4 m³/h	1,93 m³/h	1,52 m³/h	28 L	
CT67003	TM67	1"	4 m³/h	2,74 m³/h	2,15 m³/h	42 L	
CT67004	TM67	1"	4 m³/h	3,26 m³/h	2,56 m³/h	56 L	
CT67005	TM67	1"	4 m³/h	3,89 m³/h	3,05 m³/h	84 L	
CT75001	TM75	2"	10 m³/h	4,91 m³/h	3,85 m³/h	112 L	
CT75002	TM75	2"	10 m³/h	7,01 m³/h	5,49 m³/h	140 L	
CT75003	TM75	2"	10 m³/h	8,95 m³/h	7,02 m³/h	196 L	
CT77001	TM77	2"	18 m³/h	10,85 m³/h	8,50 m³/h	308 L	
CT77002	TM77	2"	18 m³/h	17,73 m³/h	13,89 m³/h	448 L	

	TYPE	VESSEL		VALVE
		A	B	C
CT67001	8x35	215 mm	897 mm	177 mm
CT67002	10x44	268 mm	1.121 mm	177 mm
CT67003	12x48	315 mm	1.244 mm	177 mm
CT67004	13x54	349 mm	1.398 mm	177 mm
CT67005	14x65	366 mm	1.674 mm	177 mm
CT75001	16x65	411 mm	1.705 mm	263 mm
CT75002	18x65	491 mm	1.722 mm	263 mm
CT75003	21x62	555 mm	1.721 mm	263 mm
CT77001	24x72	611 mm	2.168 mm	315 mm
CT77002	30x72	781 mm	2.200 mm	315 mm

