

Self-cleaning filter Semiautomatic Easy

Ref.	Description	Connection	£/uni.
FA1041	Semiautomatic filter Easy	¾"	
FA1042	Semiautomatic filter Easy	1"	
FA1043	Semiautomatic filter Easy	1¼"	
FA1044	Semiautomatic filter Easy	1½"	
FA1045	Semiautomatic filter Easy	2"	

Features system:

- Self-cleaning filter designed to ensure perfect filtration.
- Backwashing.
- Models ¾" and 1" with high flow.
- Filters 1½" and 2" have gauges incorporated in the inlet and outlet.
- Maximum temperature of 40°C.
- All materials in contact with water have DVGW certificated.
- Adjustable head.
- The maximum pressure is 16 Bar.
- AISI 316 filtration cartridge: 89 microns.
- On request: 50 - 200 - 500µm.

	FA1041	FA1042	FA1043	FA1044	FA1045
· Connection:	¾"	1"	1¼"	1½"	2"
· DN connection:	DN20	DN25	DN32	DN40	DN50
· Average flow $\Delta P=0,2b$:	5 m³/h	6 m³/h	6,5 m³/h	8 m³/h	9,5 m³/h
· Nominal pressure:	16 bar	16 bar	16 bar	16 bar	16 bar
· Max. temperature:	40°C	40°C	40°C	40°C	40°C
Weight:	2,6 kg	2,8 kg	3,1 kg	3,4 kg	3,7 kg
· Dimensions (A):	300 mm	300 mm	300 mm	300 mm	300 mm
· Dimensions (B):	261 mm	261 mm	261 mm	261 mm	261 mm
· Dimensions (C):	110 mm	110 mm	110 mm	110 mm	110 mm
· Dimensions (D):	172 mm	183 mm	188 mm	254 mm	262 mm
· Dimensions (E):	118 mm	122 mm	122 mm	128 mm	128 mm

