

Semi-industrial equipment Maxi 200/400 GPD 20"

MAXI

— 200 / 400 GPD —

| Ref. | Description | Production | £/uni. |
|--------|-----------------------|------------|--------|
| RO0200 | R.O. Maxi 200 GPD 20" | 20 L/h | |
| RO1013 | R.O. Maxi 400 GPD 20" | 40 L/h | |

Features:

- 200 GPD membrane
- Minimum pressure 1 Kg/cm²
- 20" filters
- 5µ sediment prefilter
- Activated carbon prefilter: GAC + CTO
- GAC carbon post-filter
- Transformer and pressure pump 24V
- Power supply 230V
- Optional tank

| | RO0200 | RO1013 |
|--------------------|----------|------------|
| · Production: | 20 L/h | 40 L/h |
| · Membrane: | 200 GPD | 200 GPD |
| · Membrane numbers | 1 unidad | 2 unidades |
| · Filters: | 20" | 20" |
| · Dimensions (A): | 785 mm | 880 mm |
| · Dimensions (B): | 420 mm | 420 mm |
| · Dimensions (C): | 250 mm | 250 mm |

*The equipment requires post-carbon cartridge. Is recommended 4 hours of maximum working time.



Accessories

| Ref. | Description | £/uni. |
|--------|---------------------------------------|--------|
| FS1003 | 20" 5µ polypropylene filter | 1 unit |
| FC1003 | 20" activated granular carbon filter | 1 unit |
| FC2002 | 20" activated block carbon filter | 1 unit |
| RO2040 | 200 GPD Vontron membrane 2818 | 1 unit |
| RO5003 | 200GPD 1,6LPM 24VDC AMPS booster pump | |
| RO1014 | 400GPD 2,6LPM pressure pump | |
| RO5012 | 24V 3A AC transformer | |
| RO1106 | 24V 5A 100-240V transformer | |

