

Industrial UV lamp UV multilamp

| Ref. | Description | Production £/uni. |
|--------|-------------------------|-------------------|
| UV0308 | Industrial UV multilamp | 15.900 L/h |
| UV0309 | Industrial UV multilamp | 27.250 L/h |
| UV0310 | Industrial UV multilamp | 40.880 L/h |
| UV0311 | Industrial UV multilamp | 56.780 L/h |

Features system:

- System using ultraviolet lamps to disinfect the industrial water.
- Sterilizer UV multi-lamp AISI 304 with inspection window and drain connection.
- Electrical box with electronic circuit, cable connection, working time meter through
- Indicator with LEDs indicating the status of work and service.
- Lamp with quartz sheath.
- Maximum operating pressure: 10 bar Temperature: 2 ° C 40 ° C. Power consumption: 230 V. 50 Hz

- Lamp life time: 10,000 hours.
- Possible connection with solenoid valve.



| | UV0308 | UV0309 | UV0310 | UV0311 |
|---------------------------|----------------|----------------|----------------|-----------------|
| · Production: | 15.900 L/h | 27.250 L/h | 40.880 L/h | 56.780 L/h |
| · Number UV lamps: | 2 unidades | 3 unidades | 5 unidades | 7 unidades |
| · Consumption: | 200 W | 360 W | 600 W | 840 W |
| · Connection: | DN50 | DN65 | DN80 | DN100 |
| · Diameter: | 220 mm | 273 mm | 323 mm | 400 mm |
| · Lenght: | 1.250 mm | 1.250 mm | 1.250 mm | 1.250 mm |
| · Connection: · Diameter: | DN50 220 mm | DN65 273 mm | DN80 323 mm | DN100 400 mm |