

Automatic activated carbon filters TM valves



Automatic filters features:

- Automatic cleaning valves for time.
- Vessel body made in polyester reinforced fiberglass.
- Special filters for removal of free chlorine.

- Filter media: activated carbon.
- Work pressure: 3 to 6 bar

Valve features:

- Made of noryl
- Work temperature: 4°C to 40°C
- Power supply: 230V - 12V, 50Hz.
- No water by-pass



TM67



TM75



TM77

Ref.	Valve model	Connection	Valve flow	Max. equipment flow	Silex (Kg)	Load Carbón (Kg)	€/uni.
C670015	TM67	1"	4 m³/h	0,15 m³/h	4 Kg	5 Kg	
C670030	TM67	1"	4 m³/h	0,39 m³/h	4 Kg	13 Kg	
C670050	TM67	1"	4 m³/h	0,70 m³/h	7 Kg	25 Kg	
C670080	TM67	1"	4 m³/h	1,05 m³/h	9 Kg	35 Kg	
C670100	TM67	1"	4 m³/h	1,50 m³/h	10 Kg	50 Kg	
C670125	TM67	1"	4 m³/h	1,89 m³/h	15 Kg	63 Kg	
C74170	TM75	2"	10 m³/h	2,25 m³/h	25 Kg	75 Kg	
C74200	TM75	2"	10 m³/h	3,00 m³/h	35 Kg	100 Kg	
C74350	TM75	2"	10 m³/h	4,5 m³/h	50 Kg	150 Kg	
C74500	TM77	2"	18 m³/h	6,75 m³/h	100 Kg	225 Kg	
C74750	TM77	2"	18 m³/h	9,75 m³/h	175 Kg	325 Kg	
C961150	TM96	3"	40 m³/h	14,25 m³/h	300 Kg	475 Kg	
C961450	TM96	3"	40 m³/h	18,00 m³/h	375 Kg	600 Kg	

	TYPE	VESSEL		VALVE
		A	B	C
C670015	10x17	268 mm	434 mm	177 mm
C670030	10x35	268 mm	893 mm	177 mm
C670050	12x48	315 mm	1.244 mm	177 mm
C670080	13x54	349 mm	1.398 mm	177 mm
C670100	14x65	366 mm	1.674 mm	177 mm
C670125	16x65	411 mm	1.705 mm	177 mm
C74170	18x65	491 mm	1.722 mm	263 mm
C74200	21x62	555 mm	1.721 mm	263 mm
C74350	24x72	611 mm	2.168 mm	263 mm
C74500	30x72	781 mm	2.200 mm	315 mm
C74750	36x72	932 mm	2.210 mm	315 mm
C961150	42x72	1.090 mm	2.395 mm	lateral / side
C961450	48x72	1.235 mm	2.400 mm	lateral / side

