

Self-cleaning filter

Semiautomatic Easy Max

Ref.	Description	Connection	€/uni.
FA1046	Semiautomatic filter Easy Max	2"	
FA1047	Semiautomatic filter Easy Max	2½"	
FA1048	Semiautomatic filter Easy Max	3"	
FA1049	Semiautomatic filter Easy Max	4"	

Features system:

- Self-cleaning filter designed to ensure perfect filtration.
- Backwashing.
- Gauges incorporated in the inlet and outlet.
- Maximum temperature of 60°C.
- All materials in contact with water have DVGW certificated.
- Adjustable head.
- The maximum pressure is 16 Bar.
- AISI 316 filtration cartridge: 200 microns.
- On request: 50 - 125 - 500µm.



	FA1046	FA1047	FA1048	FA1049
· Connection:	2"	2½"	3"	4"
· DN connection:	DN50	DN65	DN80	DN100
· Average flow $\Delta P=0,2b$:	32 m³/h	37 m³/h	47 m³/h	52 m³/h
· Nominal pressure:	16 bar	16 bar	16 bar	16 bar
· Max. temperature:	60°C	60°C	60°C	60°C
· Weight:	13,50 kg	15,10 kg	16,30 kg	17,30 kg
· Dimensions (A):	220 mm	220 mm	220 mm	220 mm
· Dimensions (B):	380 mm	258 mm	258 mm	258 mm
· Dimensions (C):	360 mm	360 mm	375 mm	375 mm
· Dimensions (D):	--	94 mm	100 mm	110 mm
· Dimensions (E):	99 mm	99 mm	105 mm	105 mm
· Dimensions (F):	95 mm	104 mm	110 mm	120 mm

