

## Automatic activated carbon filters Hydro valves

### Automatic filters features:

- Automatic cleaning valves for time.
- Vessel body made in polyester reinforced fiberglass.
- Special filters for removal of free chlorine.

- Filter media: activated carbon.
- Work pressure: 4 to 6 bar

### Valve features:

- Made of noryl
- Work temperature: 4°C to 40°C
- Power supply: 230V - 12V, 50Hz.
- Water by-pass



Hydro mecánica

Hydro digital

Ref.	Valve model	Connection	Valve flow	Equipment flow	Load		€/uni.
					Silex (Kg)	Carbón (Kg)	
CHM015	Mechanic Hydro	1"	4 m³/h	0,15 m³/h	4 Kg	5 Kg	
CHM030	Mechanic Hydro	1"	4 m³/h	0,39 m³/h	4 Kg	13 Kg	
CHM050	Mechanic Hydro	1"	4 m³/h	0,70 m³/h	7 Kg	25 Kg	
CHM080	Mechanic Hydro	1"	4 m³/h	1,05 m³/h	9 Kg	35 Kg	
CHM100	Mechanic Hydro	1"	4 m³/h	1,50 m³/h	10 Kg	50 Kg	
CHM125	Mechanic Hydro	1"	4 m³/h	1,89 m³/h	15 Kg	63 Kg	
CH0015	Digital Hydro	1"	4 m³/h	0,15 m³/h	4 Kg	5 Kg	
CH0030	Digital Hydro	1"	4 m³/h	0,39 m³/h	4 Kg	13 Kg	
CH0050	Digital Hydro	1"	4 m³/h	0,70 m³/h	7 Kg	25 Kg	
CH0080	Digital Hydro	1"	4 m³/h	1,05 m³/h	9 Kg	35 Kg	
CH0100	Digital Hydro	1"	4 m³/h	1,50 m³/h	10 Kg	50 Kg	
CH0125	Digital Hydro	1"	4 m³/h	1,89 m³/h	15 Kg	63 Kg	

	TYPE	VESSEL		VALVE
		A	B	C
CHM015 / CH0015	10x17	268 mm	434 mm	200 mm
CHM030 / CH0030	10x35	268 mm	893 mm	200 mm
CHM050 / CH0050	12x48	315 mm	1.244 mm	200 mm
CHM080 / CH0080	13x54	349 mm	1.398 mm	200 mm
CHM100 / CH0100	14x65	366 mm	1.674 mm	200 mm
CHM125 / CH0125	16x65	411 mm	1.705 mm	200 mm

